



for impressive performances

# ANGLE NOTCHING MACHINES

## MINI 220/4

### STANDARD EXECUTION

- Hydraulic angle notching machine with fixed angle 90°.
- Automatic blade gap adjustment.
- 2 position stops with scale, adjustable every 15°, clamping handle for intermediate positions.
- 2 mechanical plate holddowns.
- Large working table with slots and brass scales.
- Mechanical stroke adjuster.
- Transparent hand safety guards.
- Internal stop with millimetric scale.
- Footpedal control.
- Hydraulic oil.

### TECHNICAL SPECIFICATIONS

Capacity (mild steel 450 N/mm <sup>2</sup> )	4 mm
Blade length	220 mm
Angle	90°
Strokes per minute	35
Table sizes	650 x 650 mm
Motor power	2 kW
Overall dimensions	650 x 750 x 1050 mm
Weight approx.	550 kg

*Haco reserves the right to change any specifications without prior notice.*



## MAXI 250/6

### STANDARD EXECUTION.

- Hydraulic angle notching machine with fixed angle 90°.
- Automatic blade gap adjustment.
- 2 position stops with scale, adjustable every 15°, clamping handle for intermediate positions.
- 2 mechanical plate holddowns.
- Large working table with slots and brass scales.
- Mechanical stroke adjuster.
- Transparent hand safety guards.
- Internal stop with millimetric scale.
- Footpedal control.
- Hydraulic oil

### TECHNICAL SPECIFICATIONS

Capacity (mild steel 450 N/mm <sup>2</sup> )	6 mm
Blade length	250 mm
Angle	90°
Strokes per minute	35
Table sizes	900 x 700 mm
Motor power	3 kW
Overall dimensions	900 x 920 x 1100 mm
Weight approx.	800 kg

*Haco reserves the right to change any specifications without prior notice.*

